

# VC300

## HDMI to USB Video Capture Card



USB-A/USB-C



Plug and Play



Metal Casing





# Highlights

A compact USB 3.0 HDMI video capture card with 4K HDMI input and 1080P@60Hz capture for live streaming, recording, and multi-platform broadcasting. Plug-and-play and compatible with OBS, vMix, and PotPlayer.

- USB 3.0 C Male (with C Female to A Male)
- 1× HDMI 1.4b, 4K@30Hz
- Windows 7/8/10/11, MacOS, Linux, Android
- 50.4×25.1×11.7 mm (1.98×0.99×0.46")
- Plug and Play

# Package Content



# Hardware Features

|                      |                              |   |
|----------------------|------------------------------|---|
| Model Version        | VC300 1.0                    |   |
| Interfaces           | Output Interface             | 1× HDMI 1.4                                       |
|                      | Output Resolutions           | 4K (3840 x 2160) @ 30Hz                           |
|                      |                              | 2K (2560×1440) 60 Hz                              |
|                      |                              | 1080P (1920×1080) 120 Hz                          |
|                      | Video Output                 | 1× USB-C Male Connector (with C Female to A Male) |
|                      | Video Output Resolutions     | 1920 x 1080 @ 60Hz                                |
|                      | Video Output Format          | YUY2  |
|                      |                              | MJPEG   |
| USB Ports            | 1× USB-C 3.0 or 1× USB-A 3.0 |   |
| Physical             | Color                        | Silver Gray Color                                 |
|                      | Casing                       | Aluminum  |
|                      |                              | ABS   |
| Requirements         | Compatible OS                | Windows 7/8/10/11 (32/64-bit)                     |
|                      |                              | macOS   |
|                      |                              | Linux   |
| Android              |                              |   |
|                      | Driver Installation          | Driver Free                                       |
| Reliability          | Environment                  | Operating Temperature: 0~40 °C (32~104 °F)        |
|                      |                              | Storage Temperature: -10~55 °C (14~131 °F)        |
|                      |                              | Operating Humidity: 20~85% RH non-condensing      |
|                      |                              | Storage Humidity: 5~90% RH non-condensing         |
| Mechanical           | Dimension                    | 50.4×25.1×11.7 mm (1.98×0.99×0.46 inches)         |
| Package Content      | VC300                        |   |
|                      | Installation Guide           |   |
| Ordering Information | Retail Package Dimension     | 70×130×20 mm (2.76×5.12×0.79 inches)              |
|                      | Units per Carton             | 100   |
|                      | Carton Dimension             | 54×28.5×18 cm (21.26×11.22×7.09 inches)           |