

cudy



AX
3000



AX3000 Gigabit Wi-Fi 6 Mesh Router



WR3000




Up to 3.0 Gbps Wi-Fi 6 Speed: Enjoy smooth streaming, downloading, and gaming with extremely fast Wi-Fi 6 Speed.

Features

Extensive Coverage: Beamforming, and four antennas combine to deliver focused reception to devices far away.



DL/UL MU-MIMO



DL/UL OFDMA

Without OFDMA

More Devices: Wi-Fi 6 uses OFDMA to improve capacity and efficiency of your network, so more devices can connect without slowing down your Wi-Fi.



Highlights

A WiFi 6 router with four Gigabit ports, suitable for home internet up to 1000 Mbps, connecting many devices, and reducing latency.

- 1.2 GHz Dual-Core CPU
- 4-Stream Dual-Band Wi-Fi 6
- 2402 Mbps + 574 Mbps Wi-Fi
- 4× Gigabit Ethernet Ports
- Covers 130 m² (1,400 ft²)
- Cudy Mesh, VPN Server and Client
- Cudy App, Cloud Control

Package Content

- WR3000
- Power Adapter
- Ethernet Cable
- Installation Guide

Hardware Features

CPU	CPU Details	1.2 GHz Dual-Core
Memory /Storage	Flash/ROM	32 MB (256 Mbit) NOR
	DDR/RAM	128 MB (1 Gbit) DDR3
Wireless	5 GHz Wi-Fi Speed	2402 Mbps
	2.4 GHz Wi-Fi Speed	574 Mbps
	5 GHz Wi-Fi Streams	2 Spatial Streams
	2.4 GHz Wi-Fi Streams	2 Spatial Streams
	Wi-Fi Antennas	4x Fixed
	FEM or PA/LNA	5 GHz: 2× Internal
		2.4 GHz: 2× Internal
	Beamforming	√
	Range Performance	Max: 200 m (656 f)
		Tested in open-space environments with minimal interference. Actual WiFi range may vary depending on layout and wall materials. Refer to the Wall Performance specifications for placement suggestions.
		Two wooden walls with thickness < 10 cm (4")
Wall Performance		One concrete wall with thickness < 20 cm (7")
		or two concrete walls with thickness < 10 cm (4")



Hardware Specs

Interfaces	Gigabit RJ45 Ports	4
	Ethernet Notes	1× WAN port, the rest are LAN ports
	LED	System, Internet, WAN, LAN, 2.4 GHz Wi-Fi, 5 GHz Wi-Fi
	Physical Buttons	WPS Button Reset Button
Power	Power Input Type	DC Jack
	Power Methods	DC
	Power Input	12V=1A
	Power Adapter In the Box	Input: 100 ~ 240 V, 50/60 Hz Output: 12V=1A DC
	Max Power Consumption (W)	8.8w
	Idle Power Consumption (W)	2.5w
Reliability	Environment	Operating Temperature: 0 °C ~ 40 °C (32 °F ~104 °F)
		Storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F)
		Humidity: 10% ~ 90% non-condensing
		Storage Humidity: 5% ~ 95% non-condensing
Certifications	FCC, CE	
Mechanical	Installation	Desktop, Wallmount
	Dimension	183.3×109×35 mm
		7.22×4.29×1.38 inches

Ordering Information	Retail Package Dimension	240×230×60 mm
		9.45×9.06×2.36 inches
	Units per Carton	20
	Carton Dimension	49.5×32.5×48 cm 19.49×12.8×18.9 inches

Software Specs

Wireless	Wi-Fi Standards	Wi-Fi 6
	Max Wi-Fi Modulation	1024-QAM
	Wi-Fi Efficiency	OFDMA, MU-MIMO
		BSS Color
	Max Capacity	128
	Recommended Client Upper Limit	70
	Max Wi-Fi Channel Width	160 MHz
	Wi-Fi Security	WPA/WPA2/WPA3
	Guest Network	2.4 GHz, 5 GHz
General	WPS	√
	Operation Modes	Wi-Fi Router
		Access Point
		Range Extender
		WISP
		Client



Software Specs

General	Mesh	Cudy Mesh
	Mesh Backhaul	Wireless Backhaul
		Wired Backhaul
	Multi-Band Backhaul	√
	WAN Mode	DHCP
		Static IP
		PPPOE
		PPTP
		L2TP
Network	QoS	Per-User Rate Limiting
	DHCP	Address Reservation
		DHCP Client List
		Server
	IP Versions	IPv4/IPv6
	IPv6 Protocols	Relay
		Dynamic (SLAAC/DHCPv6)
		Staic (Fixed IP)
		Passthrough
		464XLAT
		MAP-E
		DS-Lite
	Multicast	√
	IPTV/VLAN	Bridge, Tag VLAN
		VoIP VLAN, IPTV VLAN

Network	TTL Customization	Extend
		Spoof
		Custom
	IGMP	IGMP Proxy
		IGMP Snooping
	Forwarding	Port Forwarding
		Port Triggering
		UPnP
		DMZ
	Firewall	SPI Firewall
		DoS Protection
		Block PING
	Application Layer Gateway	IPSec Passthrough
		L2TP Passthrough
		PPTP Passthrough
		FTP Passthrough
		TFTP Passthrough
		H323 Passthrough
SIP Passthrough		
RTSP Passthrough		
Utilities	VPN Server	WireGuard, OpenVPN
		PPTP, L2TP, IPsec
	VPN Client	WireGuard, OpenVPN
		PPTP, L2TP, IPsec



Software Specs

Utilities	DNS Options	DNS over TLS
		Manual DNS
		Rebind Protection
		Override Clients' DNS
	DNS over TLS Providers	Cloudflare
		Google
		Quad9
		Custom
	Captive Portal	√
Management	Wake on LAN	√
	Online Detection	√
	Parental Controls	Profiles Settings
		Offline Time
		Online Time
		Pause the Internet
		Web Filter
	All Devices Management	Wi-Fi Time Schedule
		MAC Filter
		IP/MAC Binding
	Per-Devices Management	Intenent On/Off
		VPN On/Off
		Online Time Schedule
		Device Rename
	Content Management	Domain Filter, IP Filter

System	Local Control Method	Config Web Page
		App Control
	Remote Control Method	Config Page via HTTPS
		App Control
		TR069/TR098/TR111/TR143/TR181
	Firmware Upgrade	Local Update
		App (Over the Air)
		Online Update
	Reliability	Timed Reboot
		Backup and Restore
	Diagnostic Tools	Diagnosis
		Ping
		Traceroute
		NSLookup
		System Log
	Languages	• English • Bengali • Catalan • Czech
		• German • Greek • Spanish • French
		• Hebrew • Italian • Croatian • Hungarian
		• Khmer • Korean • Dutch • Japanese
		• Russian • Slovak • Swedish • Romanian
		• Turkish • Vietnamese • Thai • Ukrainian
		• Polish • Norwegian • Portuguese
		• Simplified Chinese • Traditional Chinese



Software Specs

Dashboard	Panel	Internet Status
		Mesh Status
		Devices Management
		WAN Status
		LAN Status
		WISP Status
		Wi-Fi Status
		VPN Status
		DHCP Server Status
		System Version
	Charts	Mesh Topology
		Internet Speed
		WISP Speed
		Wi-Fi Speed