




Model: WR3600H

BE3600

2.5G Mesh Wi-Fi 7 Router



Easy Setup with
Cudy App





Highlights

A dual-band WiFi 7 router with an aggregate of 3.6 Gbps speed, one 2.5G WAN, one 2.5G LAN and three Gigabit LAN, catering to multi-Gig internet access, gaming, and entertainment scenarios.

- 4-Stream Dual-Band Wi-Fi 7
- 2882 Mbps + 688 Mbps Wi-Fi
- 2× 2.5GbE, 3× GbE
- Covers 130 m² (1,400 ft²)
- VPN Server and Client
- Cudy App, Cloud Control

Package Content

- WR3600H
- Power Adapter
- Ethernet Cable
- Installation Guide

Hardware Features

CPU	CPU Details	1.2 GHz Dual-Core
	Flash/ROM	128 MB (1 Gbit) NAND
Memory	DDR/RAM	256 MB (2 Gbit) DDR3
/Storage	5 GHz Wi-Fi Speed	2882 Mbps
Wireless	2.4 GHz Wi-Fi Speed	688 Mbps
	5 GHz Wi-Fi Streams	2 Spatial Streams
	2.4 GHz Wi-Fi Streams	2 Spatial Streams
	Wi-Fi Antennas	4x Fixed
	FEM or PA/LNA	5 GHz: 2× External
		2.4 GHz: 2× Internal
	Beamforming	True
	Range Performance	Max: 220 m (722 ft)
		Tested in open-space environments with minimal interference. Actual WiFi range may vary depending on layout and wall materials. Refer to the Wall Performance specifications for placement suggestions.
	Wall Performance	Two wooden walls with thickness < 10 cm (4")
		One concrete wall with thickness < 20 cm (7")
		or two concrete walls with thickness < 10 cm (4")



Hardware Specs

Interfaces	2.5G RJ45 Ports	2
	Gigabit RJ45 Ports	3
	Ethernet Notes	1× 2.5G WAN port, 1× 2.5G LAN port, 3× Gigabit LAN ports
	LED	Power
		Internet
		WAN
		LAN
		2.4 GHz Wi-Fi
		5 GHz Wi-Fi
	Physical Buttons	WPS Button
		Reset Button
Power	Power Input	DC Jack
	Power Methods	DC
	Power Input	12V=1.5A
	Power Adapter	Input: 100-240V~, 50/60Hz
		Output: 12V=1.5A
	Max Power Consumption(W)	14W
Reliability	Environment	Operating Temperature: 0 °C ~ 40 °C (32 °F ~104 °F)
		Storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F)
		Humidity: 10% ~ 90% non-condensing
		Storage Humidity: 5% ~ 95% non-condensing

Certifications	Certifications	FCC, CE
Mechanical	Installation	Desktop
		Wall-mount
	Dimension	183.3×109×38 mm
		7.22×4.29×1.5 inches
Ordering Information	Retail Package Dimension	330×256×60 mm
		12.99×10.08×2.36 inches
	Units per Carton	10
	Carton Dimension	52.8×31.7×34.7 cm
		20.79×12.48×13.66 inches



Software Specs

*Available with later firmware upgrade.

Wireless	Wi-Fi Standards	Wi-Fi 7
	Max Wi-Fi Modulation	4K-QAM
	Wi-Fi Efficiency	MLO
		MRU
		Puncturing
		OFDMA
		MU-MIMO
		BSS Color
	Max Capacity	128
	Recommended Client Upper Limit	70
	Wi-Fi Channel Width	Auto/20/40/80/160 MHz
	Wi-Fi Security	WPA/WPA2/WPA3
	Guest Network	2.4 GHz, 5 GHz
	WPS	True
General	Operation Modes	Wi-Fi Router
		Access Point
		Range Extender
		WISP
		Client
	Mesh	Cudy Mesh
	Mesh Backhaul	Wireless Backhaul
		Wired Backhaul
	Multi-Band Backhaul	True

General	WAN Mode	DHCP
		Static IP
		PPPOE
		PPTP
		L2TP
Network	QoS	Per-User Rate Limiting
		Address Reservation
	DHCP	DHCP Client List
		Server
	IP Versions	IPv4/IPv6
	IPv6 Protocols	Relay
		Dynamic (SLAAC/DHCPv6)
		Staic (Fixed IP)
		Passthrough
		464XLAT
		MAP-E
		DS-Lite
	Multicast	True
	IPTV/VLAN	Bridge
		Tag VLAN
		VoIP VLAN
		IPTV VLAN



Software Specs

Network	TTL Customization	Extend
		Spoof
		Custom
	IGMP	IGMP Proxy
		IGMP Snooping
		Port Forwarding
	Forwarding	Port Triggering
		UPnP
		DMZ
	Firewall	SPI Firewall
		DoS Protection
		Block PING
	Application Layer Gateway	IPSec Passthrough
		L2TP Passthrough
		PPTP Passthrough
		FTP Passthrough
		TFTP Passthrough
		H323 Passthrough
		SIP Passthrough
		RTSP Passthrough
Utilities	VPN Server	WireGuard
		OpenVPN
		IPsec
		Zerotier

Utilities	VPN Server	PPTP
		L2TP
	VPN Client	WireGuard
		OpenVPN
		IPsec
		Zerotier
		PPTP
		L2TP
	DNS Options	DNS over TLS
		Manual DNS
		Rebind Protection
		Override Clients' DNS
		DNS over HTTPS
	DNS over TLS Providers	Cloudflare
		Google
		Quad9
		Custom
	Wake on LAN	True
	Online Detection	True
Management	Parental Controls	Profiles Settings
		Offline Time
		Online Time
		Pause the Internet
		Web Filter



Software Specs

Management	All Devices Management	Wi-Fi Time Schedule
		MAC Filter
		IP/MAC Binding
	Per-Devices Management	Intenent On/Off
		VPN On/Off
		Online Time Schedule
		Device Rename
	Content Management	Domain Filter
		IP Filter
System	LED Control	True
	Local Control Method	Config Web Page
		App Control
	Remote Control Method	Config Page via HTTPS
		App Control
		TR069/TR098/TR111/TR181
	Firmware Upgrade	Local Update
		App (Over the Air)
		Online Update
	Reliability	Timed Reboot
		Backup and Restore
	Diagnostic Tools	Diagnosis
		Ping
		Traceroute

System	Diagnostic Tools	NSLookup
		System Log
	Languages	• English • Bengali • Catalan • Czech
		• German • Greek • Spanish • French
		• Hebrew • Italian • Croatian • Hungarian
		• Khmer • Korean • Dutch • Japanese
		• Russian • Slovak • Swedish • Romanian
		• Turkish • Vietnamese • Thai • Ukrainian
		• Polish • Norwegian • Portuguese
		• Simplified Chinese
		• Traditional ChineseInternet Status
Dashboard	Panel	Internet Status
		Mesh Status
		Devices Management
		WAN Status
		LAN Status
		Wi-Fi Status
		VPN Status
		DHCP Server Status
		System Version
	Charts	Internet Speed
		WISP Speed
		Wi-Fi Speed