Model

POE 100

30W Gigabit PoE+/PoE Injector



Datasheet

Features

- Support 1x10/100/1000M POE Port+1x10/100/1000M Ethernent Port
- Comply with IEEE 802.3、IEEE 802.3u、IEEE 802.3ab、Standards;
- Ethernet Port Supports 10/100/1000Mbps adaptive and PoE functions ;
- Support Port Auto Flip (Auto MDI/MDIX)
- Compatible with IEEE802.3af（15.4W）、IEEE802.3at（30w）
- Support AC 100-240 V power supply
- Working temperature -20~50°C
- Support wall mount

Specifications

Power	Input: AC 100-240V
Ethernet	1*10/100/1000Mbps Ethernet Port
	1*10/100/1000Mbps PoE Port
Network protocol	IEEE802.3 (10Base-T)
	IEEE802.3u (100Base-TX)
	IEEE802.3ab(1000Base-TX)
	IEEE802.3x (Flow control)
PoE Protocol	IEEE802.3af （15.4W）
	IEEE802.3at （25.4W）
Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A
	EMS: EN61000-4-2 (ESD)、EN61000-4-4 (EFT)、
	EN61000-4-5 (Surge)
	Shock: IEC 60068-2-27
	Free Fall: IEC 60068-2-32
	Vibration: IEC 60068-2-6
Network Medium	10Base-T : Cat3、4、5 or above UTP(≤100m)
	100Base-TX : Cat5 or above UTP(≤100m)
	1000Base-TX : Cat5 or above UTP(≤100m)
Power Pin Assignment	1/2(+),3/6(-)
Security Certificae	CE、FCC、RoHS

Working Environment	Working Temperature：-20~50°C
	Storage Temperature：-40~85°C
	Working Humidity：10%~90%，non-condensing
	Storage Temperature：5%~90%，non-condensing
	Working Height：Maximum10,000 feet
	Storage heigh：Maximum 10,000 feet
LED Indicators	PROT
Structure Size	Product Size：142* 55*40MM
	Package Size: 210* 160*55MM
	Product Net-Weight: 0.2KG
	Product Gross-Weight: 0.4KG
Packing Info	MEAS: 510*420*340MM
	Packing Qty: 36PCS
	Packing weight: 16 KG
Power Voltage	Input Voltage: AC 100-240 V
Package List	PoE Injector * 1 pcs
	User Manual * 1 pcs
	Power Cable * 1pcs