



Model

GS 2024S2

24-Port Gigabit Managed Switch
with 4 SFP Slots



1.Product Overview

28-Port Managed Gigabit Ethernet Switch, black iron shell design, built-in DC 12V Power supply, light and simple, with LED indicator on the panel, can dynamically display the connection and operation of equipment, provide simple fault detection methods, and facilitate maintenance and management; this series of switches provide advanced network management functions: redundant ring network, VLAN, cluster, QoS, speed control, port image, fault alarm and firmware online upgrade. The adaptive port can automatically adapt to the 10m, 100m and 1000m networks, and can automatically adapt to the full duplex or half duplex mode; the MAC address self-learning function ensures error free data transmission; the store and forward mode prevents the damaged packets from flooding in the network; the flow control function can prevent the impact of a large amount of instantaneous data on the network; the port supports MDI/ Mdx auto flip function, non-blocking line speed transmission of all ports.

It is mainly located in the core or convergence layer of user networks such as industrial parks, buildings, factories and mines, government agencies, community broadband, etc.; it can be widely used in Ethernet access scenarios such as small and medium-sized enterprises, Internet cafes, hotels, schools, etc.

2. Product Features

1. Support 24* Gigabit Ethernet Ports+ 4* Gigabit SFP Ports+1* Console Port
2. SupportIEEE802.3, IEEE802.3i, IEEE802.3u, IEEE802.3ab, IEEE802.3z, Storage and forwarding
3. Ethernet ports support 10/100/1000M adaptive
4. Adopt store-and-forward switching mechanism
5. Adopt store-and-forward switching mechanism
6. Fanless design, natural Cooling, 1U Rack Mount
7. Support 802.1x port authentication, support AAA authentication, support TACACS+ authentication
8. Support WEB, TELNET, CLI, SSH, SNMP, RMON management

3. Specification

| | |
|------------------------|----------------------------|
| Model | GS2024S2 |
| Power | AC INPUT (100-240V) |
| Ethernet | 24* Gigabit Ethernet Ports |
| | 4* Gigabit SFP Ports |
| | 1* Console Port |
| Bandwidth | 56Gbps |
| Packet Forwarding Rate | 41.66Mpps |
| Package Cache | 4Mb |
| Memory | 128M |
| Flash Memory | 16M |
| MAC Address | 8K |
| VLANs | 4096 |
| Jumbo Frame | 9.6Kbytes |
| Transfer Mode | Storage & Forwarding |
| MTBF | 100000 Hours |

| Standard | |
|-------------------|--|
| Network Protocol | IEEE802.3 (Ethernet) |
| | IEEE802.3u (Rapid Ethernet) |
| | IEEE 802.3ab (Gigabit Ethernet) |
| | IEEE 802.3z (Gigabit Ethernet Optic Fiber) |
| | IEEE802.3x (Flow Control) |
| | IEEE 802.3az (Energy-efficient Ethernet) |
| | IEEE 802.3ad (Link aggregation) |
| | IEEE 802.1AB LLDP/LLDP-MED (Link Layer Discovery Protocol) |
| | IEEE 802.1D Spanning Tree Protocol STP |
| | IEEE 802.1w Rapid Spanning Tree Protocol RSTP |
| | IEEE 802.1s Multiple Spanning Tree Protocol MSTP |
| | IEEE 802.1Q (Virtual LAN) |
| | IEEE 802.1p (VLAN Label) |
| | IEEE 802.1X (User authentication) |
| Optical Medium | Multi-mode fiber: 50/125, 62.5/125, 100/140um |
| | Single mode fiber: 8/125, 8.7/125, 9/125, 10/125um |
| Network Medium | 10Base-T: Cat 3, 4, 5 or above UTP(≤100m) |
| | 100Base-TX: Cat 5 or above UTP(≤100m) |
| | 1000Base-TX: Cat 5 or above UTP(≤100m) |
| Industry Standard | EMI: FCC Part 15 CISPR (EN55032) class A |
| | EMS: EN61000-4-2 (ESD), |
| | EN61000-4-4 (EFT), |
| | EN61000-4-5 (Surge) |

| Environment Standard | |
|----------------------|---|
| Working Environment | Working Temperature: -10~50℃ |
| | Storage Temperature: -40~70℃ |
| | Working Humidity: 10%~90%, non-condensing |
| | Storage Temperature: 5%~90%, non-condensing |
| Function Indicator | |
| Indicator | PWR(Power Indicator); |
| | SYS(System Light); |
| | Link/Act(Link & Data) |
| PWR | On: Powered On |
| | Off: Powered Off |
| SYS | Off: System Off |
| | On: System On |
| Link/ACT | On: No Data |
| | Flashing: Data Transmit |
| | Off: Link Connection Blocked |

| Physical Specification | |
|------------------------|--|
| Structure Size | Product Size: 440*204*44mm |
| | Package Size: 500*290*85mm |
| | Product N. W: 2.45kg |
| | Product G. W: 3.06kg |
| Packing Info | MEAS: 520*445*310MM |
| | Packing Qty: 5PCS |
| | Packing Weight: 16.3 KG |
| Power Voltage | Machine Input Voltage: AC 100-240V; |
| | Built-in power output: DC12V3A; Total Power: 36W |
| Package List | Switch: 1PCS; |
| | Power cable: 1PCS; |
| | Serial cable: 1PCS; |
| | Instruction manual: 1PCS; |
| | Certificate of quality: 1PCS; |
| | Warranty card: 1PCS; |
| | Mounting ear: 1 Pair |

| Layer 2 Software Function | |
|---------------------------|--|
| Port Management | Enable/Disable Port |
| | Speed, Duplex, MTU Setting |
| | Flow-control |
| | Port Information Check |
| Port Mirroring | Supports both side-way port mirroring |
| Port Speed Limit | Support port rate limiting, the granularity of |
| | rate limiting is 32Kbps |
| Port Isolation | Support port isolation Settings |
| Storm Suppression | Supports unknown unicast, unknown multicast, |
| | and broadcast storm suppression |
| Link Aggregation | Support static manual aggregation |
| | Support LACP dynamic aggregation |
| | Access |
| VLAN | Trunk |
| | hybrid |
| | Support VLAN division based on port, protocol, |
| | and MAC address, VLAN tunnel |
| | Support GVRP dynamic VLAN registration |
| | Voice VLAN |
| MAC | Support static addition, deletion |
| | MAC address learning limit |
| | Support dynamic aging time setting |
| Spanning Tree | 802.1D Spanning Tree Protocol (STP) |
| | 802.1w Rapid Spanning Tree Protocol(RSTP) |
| | 802.1s Multi Spanning Tree Protocol(MSTP) |
| Multicast | Support static addition, deletion, IGMP-snooping |
| | Support MLD-Snooping |
| | Support v1/2/3 dynamic multicast monitor |
| DDM | Support SFP/SFP+DDM |

| | |
|--------------------------|--|
| Layer 3 Function | |
| Routing Function | Static routing |
| IP | IPv4, IPv6 Interface |
| ARP | Support ARP |
| Extended Function | |
| ACL | Based on source MAC, destination MAC, protocol type, source IP, destination IP, L4 port |
| QOS | Based on 802.1p (COS) classification |
| | Based on DSCP classification |
| | Classification based on source IP, destination IP, and port number |
| | Support SP, WRR scheduling strategy |
| | Support flow rate limit CAR |
| LLDP | Support LLDP link discovery protocol |
| User Setting | Add/delete users |
| Log | User login, operation, status, events |
| Anti-attack | DOS Defense |
| | Support CPU protection and limits the rate of sending CPU packets |
| | ARP binding (IP, MAC, PORT binding) |
| Certification | Support 802.1x port authentication |
| | Support AAA certification |
| Network diagnosis | Support ping, telnet, trace |
| System Management | Device reset, configuration save/restore, upgrade management, time setting, etc |

| | |
|----------------------------|---|
| Management Function | |
| CLI | Support serial port command line management |
| SSH | Support SSHv1/2 remote management |
| TELNET | Support telnet remote management |
| WEB | Support Layer 2 settings, Layer 2 and Layer 3 monitor |
| SNMP | SNMP V1/V2/V3 |
| | Support trap: ColdStart, WarmStart, LinkDown, LinkUp |
| RMON | Support RMON v1 |
| Other Functions | Support DHCP Snooping, Option82, DHCP Server |
| | Support dynamic ARP detection |
| | Support TACACS+ certification |
| | Support DNS Setting |
| | Support port security setting |
| | Support MVR protocol |
| | Support cable detection VCT function |
| | Support UDLD protocol |